

Model		CGK015V3L-B	CGK025V3L-B	CGK030V3L-B	CGK-025V3L-B	CGK-030V3L-B	CGK-040V3L-B	CGK-050V3L-B	CGK-060V3L-B	
		Jednofazowe ~230V 50Hz +-10%				Trójfazowe ~400V 50Hz +-10%				
Max. Tepelný výkon (A7W35)	kW	6	9.4	11.6	9.4	11.5	15.8	19.8	21.8	
C.O.P (A7W35)	W/W	4.62	4.56	4.41	4.56	4.42	4.62	4.72	4.62	
Tepelný výkon Min./Max. (A7W35)	kW	2.76/6	4.32/9.40	5.336/11.6	4.37/9.5	5.52/12	6.9/15	9.2/20	10.12/22	
Příkon Min./Max.(A7W35)	W	478/1299	750/2061	968/2630	755/2052	999/2715	1195/3247	1559/4237	1752/4762	
C.O.P Min./Max.(A7W35)	W/W	4.62/5.78	4.56/5.70	4.41/5.51	4.63/5.79	4.42/5.53	4.62/5.78	4.72/5.90	4.62/5.78	
Max.Tepelný výkon(A7W45)	kW	5.8	9.1	11.1	9.1	11.5	14.4	19.2	21.1	
C.O.P (A7W45)	W/W	3.70	3.70	3.53	3.70	3.54	3.70	3.78	3.70	
Tepelný výkon Min./Max.(A7W45)	kW	2.65/5.76	4.20/9.12	5.12/11.14	4.20/9.12	5.30/11.52	6.62/14.40	8.83/19.20	9.72/21.12	
Příkon Min./Max.(A7W45)	W	604/1558	956/2468	1223/3156	954 /2462	1262/3258	1509/3896	1970/5085	2214/5714	
C.O.P Min./Max.(A7W45)	W/W	3.70/4.39	3.70 /4.39	3.53/4.19	3.70/4.40	3.54/4.20	3.70/4.39	3.78/4.48	3.70/4.39	
Ma x výkon chlazení A35W18)	kW	5.5	8.7	10.6	8.7	10.9	13.7	18.2	20.1	
E.E.R (A35W18)	W/W	3.59	3.59	3.42	3.59	3.43	3.59	3.66	3.59	
Výkon chlazení Min./Max.(A35W18)	kW	2.52/5.47	3.99/8.66	4.87/10.58	3.99/8.66	5.03/10.94	6.29/13.68	8.39/18.24	9.23/20.06	
Příkon Min./Max.(A35W18)	W	585/1784	927/2824	1185/3613	925/2818	1223/3729	1463/4459	1909/5820	2146/6540	
E.E.R Min./Max.(A35W18)	W/W	3.07/4.30	3.07/4.30	2.93/4.11	3.07/4.31	2.93/4.12	3.07/4.30	3.13/4.39	3.07/4.30	
Ma x výkon chlazení A35W7)	kW	4.3	6.8	8.4	6.8	8.6	10.8	14.4	15.8	
E.E.R(A35W7)	W/W	2.69	2.69	2.57	2.69	2.57	2.69	2.75	2.69	
Výkon chlazení Min./Max.(A35W7)	kW	1.99/4.32	3.15/6.84	3.84/8.35	3.15/6.84	3.97/8.64	4.97/10.80	6.62/14.40	7.29/15.84	
Příkon Min./Max.(A35W7)	W	525/1657	831/2623	1063/3356	829/2618	1098/3463	1313/4142	1713/5405	1925/6075	
E.E.R Min./Max. (A35W7)	W/W	2.61/3.79	2.61/3.79	2.49/3.61	2.61/3.79	2.49/3.62	2.61/3.79	2.66/3.87	2.61/3.79	
Jmenovitý proud	A	6.2	9.8	12.6	4.3	5.7	6.9	8.9	10.0	
Maximální příkon	kW	1.9	3.0	3.8	3.0	3.9	4.7	6.1	6.9	
Maximální proud	A	9.01	14.27	18.25	6.28	8.31	9.93	12.97	14.57	
KOMPRESOR Typ		Panasonic, Twin Rotary BLDC compressor								
Ventilátor	Počet	1				2				
	Průtok vzduchu	m3/h	1500	2500	3000	2500	3000	3500	5000	5500
	Výkon	W	30	80	100	80	100	120	200	210
Výměník tepla	Typ	Deskový výměník tepla								
	Tlaková ztráta	kPa	18	18	20	18	20	23	23	25
	Spojení cze	cal	G3/4"	G1"	G1"	G1"	G1"	G1"	G1"	G1"
Požadovaný průtok	Min./Nom./Max.	L/S	0.18 0.29 0.48	0.28 0.45 0.76	0.35 0.55 0.92	0.28 0.45 0.76	0.36 0.57 0.96	0.45 0.72 1.19	0.60 0.96 1.59	0.66 1.05 1.75
Hlučnost čerpadla	dB(A)	49	56	59	56	59	60	61	62	
Rozměry netto D×H×V	mm	990*375*655	1110*475*810	1110*475*810	1110*475*810	1110*475*810	1110*475*960	1110*475*1355	1110*475*1355	
Rozměry balení DxHxV	mm	1070*405*800	1200*540*970	1200*540*970	1200*540*970	1220*540*970	1200*540*1120	1200*540*1510	1200*540*1510	
Hmotnost netto	Kg	52	78	88	78	88	98	124	124	
Hmotnost balení	Kg	58	106	116	106	116	126	161	161	